



**PETRON  
PLUS™  
FORMULA 7**



## PETRON PLUS™ FORMULA 7 LEAD SUBSTITUTE

▶ **PART NO.'S: 55360, 55362, & 55363**

**TECHNICAL DATA SHEET**

Petron Plus™ Formula 7 Lead Substitute (Off-Road) was formulated do to the phaseout of leaded gasoline initiated by the EPA, and the lowering of octane rating from 89 to 87. The effects of this phaseout will have potential adverse effect on performance. More serious, however, is the danger of engine damage and possible failure without the valve lubricating effect of lead antiknock.

Under certain operating conditions, exhaust valve seats will wear excessively, when an engines that is designed to run on leaded gasoline is operated on unleaded gasoline or gasoline containing an insufficient amount of lead antiknock.

Valve seat recession is the process that involves formation of hard, iron oxide deposits, or lumps, on the valve face— followed by local welding to the valve seat, then separation and removal of metal from the valve seat. As the cycle continues, the valve seat recedes into the cylinder head, resulting in a loss of compression and power.

Available in 10 ounce bottles, 5 gallon pails, & 54 gallon drums.

### APPLICATIONS:

1. All Engines Designed for Leaded Gasoline.

### FEATURES:

1. Helps Protect Against Valve Seat Recession.
2. Controls Deposits Build-up. Will Not Create Deposits on Other Important Engine Parts.
3. Helps Reduce Engine Knock, Ping and Run-On.

### BENEFITS:

1. Reduces Maintenance Cost.
2. Lowers the Engine Octane Requirements.

**PETRON PLUS™ GLOBAL, INC.**

P.O. BOX 1906 HUTCHINSON, KS 67504 USA, 620/663-1800 Phone, 620/663-8560 Fax,  
www.petronplus7.com www.petronplusglobal.com

**TYPICAL SPECIFICATIONS:**

**PETRON PLUS™**  
**FORMULA 7**  
**LEAD SUBSTITUTE**

Part No.,	.	.	.	.	.	.	.	.	.	.	.	55360, 55362, & 55363
Specific Gravity,.	.	.	.	.	.	.	.	.	.	.	.	0.781
Pounds/U.S. gal. at 60°F.,	.	.	.	.	.	.	.	.	.	.	.	.665
Flash Point, COC, °F.,	.	.	.	.	.	.	.	.	.	.	.	142
Pour Point, °F.,	.	.	.	.	.	.	.	.	.	.	.	-80
Color, ASTM D-1500,	.	.	.	.	.	.	.	.	.	.	.	1.5

**DIRECTIONS**

**10 ounces Treats 10 gallons of gasoline.**

**Add to gasoline when gas tank is nearly empty. Dispose of empty container properly. Refuel with up to 18 gallons of gasoline.**

**Distributed By:**

**December., 2010**

Warranty: All products purchased from Petron Plus Global, Inc., (PPGI) are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading. PPGI warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by PPGI is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine the product's suitability for a particular purpose. No warranty is expressed or implied regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose, or that the use of such other information or product will not infringe any patent.