



PETRON PLUS™ FORMULA 7



PETRON PLUS™ FORMULA 7 HEAVY-DUTY MULTI-PURPOSE FLEET, & INDUSTRIAL GREASE

▶ **PART NO.'S: 00550, 00552, 00553, & 00554**

TECHNICAL DATA SHEET

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease is the latest technological advance in grease.

Although Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease is the premium grease for all applications, whether on-road, off-road, lake, or salt water, it can also be used as an industrial grease with excellent shear stability, load carrying ability, water resistance, rust resistance and oxidation resistance.

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease is free of heavy metals and resists burning.

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease will provide excellent performance in severe high temperatures applications, with light or heavy loads, and under wet or dry conditions

Petron Plus™ Formula 7 Heavy-Duty Multi-Purpose Fleet & Industrial Grease is compatible with a wide variety of seal materials, such as Nitrile, Viton and Neoprene.

This product has a 600°+ Dropping point, a Timken OK load of 70 lbs. and a weld point of 800 kg.

APPLICATIONS:

1. Heavy-Duty Fleets.
2. Commercial & industrial applications.
3. Marine applications.
4. Lake or salt water applications.
5. Automotive and industrial applications.
6. Construction equipment.
7. Where a NLGI 2 grease is required.

FEATURES:

1. A Calcium Sulfonate Complex.
2. NLGI 2
3. Extremely High Temperature Performance.
4. Dropping Point of 600°F+.
5. Timken OK Load of 70 lbs.
6. Four Ball EP Weld of 800 kg.
7. Excellent water resistance.

BENEFITS:

1. Contains no heavy metals.
2. Long life grease.
3. Reduced maintenance costs.
4. Heavy Load Carrying Capabilities..
5. Highly water resistance.

PETRON PLUS™ GLOBAL, INC.

P.O. BOX 1906 HUTCHINSON, KS 67504 USA, 620/663-1800 Phone, 620/663-8560 Fax,
www.petronplus7.com

www.petronplusglobal.com

TYPICAL SPECIFICATIONS:

PETRON PLUS™
FORMULA 7
HEAVY-DUTY MULTI-PURPOSE FLEET, & INDUSTRIAL GREASE

Part No.,	00550, 00552, 00553, & 00554
Thickener,	Calcium Sulfonate Complex
NLGI, Consistency Grade, ASTM D-217,	2
Texture,	Smooth
Dropping Point, °F, ASTM D-2265,	600+
PENETRATION	
Unworked, ASTM D-217,	285
100,000 Strokes change from 60 strokes, ,	± 20
Flash Point, COC, °F,	>480
Fire Point, °F. ASTM D-92,	>520
Wheel Bearing Leakage, GM, ASTM D-1263,	0.4
Water Washout, @ 175°F, mass %, Max, ASTM D-1264,	1.5
Water Spray Off, %, Max, ASTM D-4049,	7.2
Oil Separation, 25°C, 24 hrs, %, ASTM D-1742,	0
Oxidation Stability, PSI drop 100 Hrs., ASTM D 942,	1.5
Timken OK Load, lbs, ASTM D-2509,	70
Four Ball EP Weld, kgf, ASTM D-2596,	800
Four Ball Wear Scar, mm, ASTM D-2266,	0.40
DI Rust Protection, ASTM D-1743,	Pass
OIL VISCOSITY	
@ 400°C, cSt, ASTM D-445,	460
Viscosity Index, ASTM D-2270,	97+
Pounds per gallon,,	8.16
Color,	Aqua Green

Available in 14 ounce tubes, 35 lbs pails, 120 lb keg, & 400 lbs drums.

Distributed By:

December., 2010

Warranty: All products purchased from Petron Plus Global, Inc., (PPGI) are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading. PPGI warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by PPGI is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine the product's suitability for a particular purpose. No warranty is expressed or implied regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose, or that the use of such other information or product will not infringe any patent.